



S2003

1K Plastic Primer / Adhesion Promoter

Description	<p>S2003 1K Plastic Primer is a transparent, fast drying, universal, ready to use plastic primer it is used for preparing the surfaces of all plastics prior to the application of colour.</p> <p>Using S2003 1K Plastic Primer surfaces avoids the need to identify plastics before coating, it is particularly effective at promoting adhesion to difficult to coat plastics such as TPO's.</p>
Surface preparation and instructions for use	Thoroughly clean and degrease surfaces with a suitable plastic cleaner such as U-POL PlastX 1.
Health and Safety Statement	<p>FOR PROFESSIONAL USE ONLY. Read full instructions before use.</p> <p>IMPORTANT: This product contains hazardous materials and therefore appropriate personal protective equipment should always be used. Please refer to the label and consult the material safety data sheet for full handling instructions and personal protection information. These are available via your local stockist or via the U-POL website at WWW.U-POL.COM. U-POL disclaim any liability where the user does not wear the recommended personal protective equipment.</p>
Application	<p>Shake can thoroughly before use.</p> <p>Apply 1-2 light even coats.</p> <p>Allow 5-10 minutes flash off time between coats.</p>
Drying Time	<p>Allow 20 mins at 20°C, 10 mins at 60°C before overcoating.</p> <p>Drying time is dependent upon film thickness, humidity and temperature.</p>
Overpainting	S2003 1K Plastic Primer should be directly overcoated within 1 hour of application with a suitable primer filler or surfacer.
Product Code	S2003/1 - 1 litre can

U-POL, 1 TOTTERIDGE LANE, WHETSTONE, LONDON, N20 0EY, UK
Home Sales T: +44(0)870 899 8200; F:+44(0)870 899 8211; E: sales@u-pol.com;
Export Sales T: +44(0)870 899 8200; F:+44(0)870 899 8299; E: exportsales@u-pol.com;
Technical T: +44(0)870 899 8310; F:+44(0)870 899 8351; E: technicaldepartment@u-pol.com;
WEBSITE: WWW.U-POL.COM